



Sample image

CA20R

Type Size: S0

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Screw terminal

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage U_i

Voltage (V)	AC / DC
690	AC

Rated impulse withstand voltage U_{imp}

Voltage (kV)	Overvoltage category	Pollution degree	Supply system	Function
6	III	3	Valid for lines with grounded common neutral termination	switch

Rated uninterrupted current I_u /Ith

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
25	55	60	Ambient temperature +55°C during 24 hours with peaks up to +60°C

Conventional enclosed thermal current I_{the}

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	Additional requirements	No. of stages (from - to)	Mounting	Mounting size
25	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C	--	--	--

Rated operational current I_e

Utilization category	Voltage (V)	Current (A)
AC-15	220 - 240	8
AC-15	380 - 440	5
AC-20A	690	25
AC-21A	20 - 690	25
AC-22A	220 - 500	25
AC-22A	660 - 690	25

Rated operational power

Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-2	220 - 240	3	3	5,50
AC-2	380 - 440	3	3	11
AC-2	500 - 500	3	3	15
AC-2	660 - 690	3	3	13
AC-3	220 - 240	3	3	4
AC-3	380 - 440	3	3	7,50
AC-3	500 - 500	3	3	7,50
AC-3	660 - 690	3	3	7,50
AC-3	110 - 120	1	2	1,50
AC-3	220 - 240	1	2	3
AC-3	380 - 440	1	2	3,70
AC-4	220 - 240	3	3	1,50
AC-4	380 - 440	3	3	3
AC-4	500 - 500	3	3	3
AC-4	660 - 690	3	3	3
AC-4	110 - 120	1	2	0,45
AC-4	220 - 240	1	2	1,10
AC-4	380 - 440	1	2	2,20
AC-23A	220 - 240	3	3	5,50
AC-23A	380 - 440	3	3	11
AC-23A	500 - 500	3	3	11
AC-23A	660 - 690	3	3	11
AC-23A	110 - 120	1	2	1,50
AC-23A	220 - 240	1	2	3
AC-23A	380 - 440	1	2	5,50

Max Fuse Rating IEC

Fuse characteristic	No. of Fuses	Current (A)
gG	1	35

UL60947-4-1, UL508
Rated insulation voltage Ui

Voltage (V)	AC / DC
600	AC

Rated thermal current

Current (A)	Ambient temperature (°C)	Additional Text
30	0 - 40	-

CSA
Rated insulation voltage Ui

Voltage (V)	AC / DC
600	AC

Rated thermal current

Current (A)	Ambient temperature (°C)	Additional Text
30	0 - 40	-

GENERAL TECHNICAL INFORMATION
Tightening torque of screws

tightening torque (Nm)	tightening torque (lb-in)
1	9

Rated short-time withstand current Icw

Time (s)	Current (A)
1	280

Size of conductor

composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm ²) or (AWG/kcmil)	Material of the wire
flexible wire	Max.	2	AWG 12	Copper
flexible wire	Max.	2	4mm ²	Copper
Single-core or stranded wire	Max.	2	AWG 10	Copper
Single-core or stranded wire	Max.	2	4mm ²	Copper
flexible wire with ferrule according to DIN 46228	Max.	2	2.5mm ²	Copper

Approbations
Specification
Marking

CE marking


UK Directives

IEC 60947-3; EN 60947-3; VDE 0660 Teil107

IEC 60947-3
EN 60947-3

UL 60947-4-1; CSA C22.2 No. 60947-4-1



CSA C.22.2 No.14


Power loss per pole

Power (W)
0,90

Conditions during transport and storing

Minimum temperature (°C)	Maximum temperature (°C)	additional requirements
-40	85	In case of temperatures below -5°C no shock load permissible

General Information
Text

- Do not lubricate or treat contacts.
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.
- Use copper wire only. Do not coat the wire end with tin.
- Terminals with factory fitted jumper links are tightened during production. Take care during installation to ensure factory fitted links are not lost by undoing both sides of linked terminals. After wiring, all terminal screws must be tightened to recommended torque specifications.
- After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.

Operating temperature

Min. Temperature [°C]	Max. Temperature [°C]
-5	60